

VESDA SENSEPOINT XCL

MICRO BORE



Aspirated Gas Detection for Micro Bore ASD System (VESDA-E VEA Addressable Aspirating Smoke Detection)

Xtralis the manufacturer of the market leading VESDA Aspirating Smoke Detection (ASD) technology has developed with its sister company Honeywell Analytics a new concept of aspirated gas detectors. When used with the VESDA-E VEA; VESDA Sensepoint XCL provides early warning of the presence of gases for occupant protection and system monitoring whilst at the same time ensuring protection against fire threats. Through its embedded Bluetooth interface, customers can pair the VESDA Sensepoint XCL detector with their smart device to perform installation, commissioning and maintenance, allowing faster detector configuration, simplified operation and service.



Applications include

- Residential
- Commercial premises
- Hospitals
- Hotels
- Car parks (underground / enclosed)
- Laboratories
- High tech manufacturing
- Universities and schools
- Chemical / Pharmaceutical
- Indoor air quality monitoring
- Battery rooms
- Fuel storage areas
- Confined spaces
- Food & beverage
- Refrigerated systems (leak detection)
- Greenhouses


Installation

VESDA Sensepoint XCL is designed to be inserted in-line to the VESDA-E VEA microbore tube network using flexible tubes as shown below:


Insert the calibration/flow cap into the detector module and turn clockwise until locked into place.



Insert the supplied flexible tubes (cut to 50mm (2 in) length) over the full length of both nozzles of the calibration / flow cap.



Insert VEA tubes at least 15mm (0.6 in) into flexible tubes. Secure VEA and flexible tubing parts with the supplied tube clips.



Features

- Available Sensors:
 - Carbon Monoxide (CO): 300ppm (adjustable 50 – 1000ppm)
 - Combustible (CAT): 0 – 100% LEL (Methane, Hydrogen, Propane, Ethanol, Butane, Octane, etc.)
 - Hydrogen (H₂): 1000ppm
 - Carbon Dioxide (CO₂): 5.0% v/v (adjustable 1.0 – 5.0% v/v)
 - Carbon Dioxide (CO₂): 5000ppm (adjustable 1000 – 5000ppm)
- Factory calibrated detector
 - (CAT: Factory calibrated to CH₄)
- Integral alarm status LEDs
- Wireless Interface: Bluetooth 4.0 (Bluetooth Low Energy)
 - Connect up to 10m away (mobile device dependent). Use compatible smart device running iOS 10 / Android 4.3 or above
- Integrates with PLCs/HVAC/BMS/FACP
- Configurable relays
- 4-20 mA analog outputs or RS 485 Modbus output
- VSC and VSM4 integration for remote access to detectors (Modbus version) operating status

Tube Size Compatibility

- Connects to VESDA-E VEA micro bore tube 6 mm (1/4") OD using flexible tubes (supplied)

Approvals

- Electrical safety
 - Conforms to EN/UL/IEC61010-1
 - Certified to CSA-C22.2 No. 61010-1-12
- CE - EMC
 - EN 50270
- RADIO
 - RED, FCC, BT SIG
- OTHERS
 - UL2075 (CO and CH₄), AS 1668.2

VESDA SENSEPOINT XCL

TECHNICAL SPECIFICATIONS



How it works

VESDA Sensepoint XCL can be added to existing or new VESDA-E VEA installations to actively monitor the presence of gases. It integrates with other building systems, including fire alarm control panels, PLCs, HVAC and building management systems, and provides real-time situational awareness for intelligent emergency response.

VESDA Sensepoint XCL is capable of remote sampling up to 100 m (328 ft) providing significant installation and routine maintenance cost savings with easy access to the detector unit for diagnostic information and servicing. Sensor cartridges are easily replaced in the field through simple steps.

Flexible Output Options

VESDA Sensepoint XCL is available with either a 4-20 mA analog output or Modbus RTU, both versions being equipped with 2 programmable relays. The result is a flexible solution that can be easily incorporated into legacy systems as well as new installations. For VESDA Sensepoint XCL (Modbus version) installations requiring additional detector relay outputs, users can opt to network detectors to the VESDA Sensepoint 301C Gas Controller (Data Sheet (Doc. No. 36443), Installation Manual (Doc. No. 36442)).

VESDA Sensepoint XCL Ordering Information

VESDA Sensepoint XCL – Micro Bore ASD System gas detectors come complete with the main detector unit (pre-installed with sensor cartridge), two cable glands, calibration/flow cap, flexible tube and tube clips to connect to VEA tubing. Two variants are available based on detector outputs (mA analog, Modbus RTU).

Specifications

| | |
|--|---|
| Supply Voltage | 24 V DC nominal 11 to 32 V DC (Analog 4-20 mA) 9 to 32 V DC (Modbus) 24 V AC 50/60Hz Nominal (20 to 27 VAC) |
| Maximum Power Consumption (24 V DC) | Analog 4-20 mA: 1.2 W (Toxic) 2.7 W (CAT - flammable) 1.7 W (CO ₂) Modbus: 0.7 W (Toxic) 2.2 W (CAT - flammable) 1.2 W (CO ₂) Relay Version: additional 0.6 W total |
| Maximum Inrush Current (24 V DC) | 850 mA |
| Dimensions (WxHxD) | 113 x 113 x 59 mm (4.4 x 4.4 x 2.3 in) |
| Weight | 500 g (1.1 lb) |
| Ingress Protection Rating | IP65, Type 4 (NEMA 250) |
| Casing Material | Polycarbonate (charcoal colour) |
| Operating Conditions | Operating Temperature: -20 to +50 °C (-4 to +122 °F) Storage Temperature: 0 to +30 °C (+32 to +86 °F) Humidity: 0 to 99% (non-condensing) <i>Flammable catalytic versions: 10 to 90% RH. Operating the detector outside this range may result in increased drift and a reduction in detector accuracy.</i> |
| Atmospheric pressure | 95 to 110 kPa |
| Wire/Terminal size | Pluggable rising clamp style. 0.5 to 1.5 mm ² , 20 to 16 AWG. |
| Output | Analog Output: 0 to 23 mA Digital Output: Modbus RTU Relay Output: 2 relays (24 V DC / 250 V AC, 5 A) |

Ordering Codes

| Ordering Code | Description |
|------------------|--|
| XCL-VEA-CO-RA | VESDA Sensepoint XCL CO 300ppm 4-20mA Relay for VEA |
| XCL-VEA-CO-RM | VESDA Sensepoint XCL CO 300ppm Modbus Relay for VEA |
| XCL-VEA-CH4-RA | VESDA Sensepoint XCL CH ₄ 0-100% LEL 4-20mA Relay for VEA |
| XCL-VEA-CH4-RM | VESDA Sensepoint XCL CH ₄ 0-100% LEL Modbus Relay for VEA |
| XCL-VEA-H2-RA | VESDA Sensepoint XCL H ₂ 1000ppm 4-20mA Relay for VEA |
| XCL-VEA-H2-RM | VESDA Sensepoint XCL H ₂ 1000ppm Modbus Relay for VEA |
| XCL-VEA-CO2VV-RA | VESDA Sensepoint XCL CO ₂ 5% v/v 4-20mA Relay for VEA |
| XCL-VEA-CO2VV-RM | VESDA Sensepoint XCL CO ₂ 5% v/v Modbus Relay for VEA |
| XCL-VEA-CO2PP-RA | VESDA Sensepoint XCL CO ₂ 5000ppm 4-20mA Relay for VEA |
| XCL-VEA-CO2PP-RM | VESDA Sensepoint XCL CO ₂ 5000ppm Modbus Relay for VEA |
| XCL-VEA-CO-RA-5 | 5 x VESDA Sensepoint XCL CO 300ppm 4-20mA Relay for VEA |
| XCL-VEA-CH4-RA-5 | 5 x VESDA Sensepoint XCL CH ₄ 0-100% LEL 4-20mA Relay for VEA |
| XCL-VEA-H2-RA-5 | 5 x VESDA Sensepoint XCL H ₂ 1000ppm 4-20mA Relay for VEA |

Spare Parts

| Ordering Code | Description |
|---------------|--|
| XCL-FILTER | VESDA Sensepoint XCL Replacement Filter - Pack of 10 |
| XCL-VEA-CAL | VESDA Sensepoint XCL Calibration/Flow Cap for VEA |
| XCL-M20-CG | VESDA Sensepoint XCL Cable Glands - Pack of 10 |
| XCL-VEA-TUB | VESDA Sensepoint XCL Tubing Interface for VEA |
| XCL-COVER | VESDA Sensepoint XCL Sensor Cover with Gasket |
| XCL-XRL-SC-CO | VESDA Sensepoint XCL/XRL Replacement Sensor - CO 300ppm |
| XCL-SC-CH4 | VESDA Sensepoint XCL Replacement Sensor - CH ₄ 0-100% LEL |
| XCL-XRL-SC-H2 | VESDA Sensepoint XCL/XRL Replacement Sensor - H ₂ 1000ppm |
| XCL-SC-CO2VV | VESDA Sensepoint XCL Replacement Sensor - CO ₂ 5% v/v |
| XCL-SC-CO2PP | VESDA Sensepoint XCL Replacement Sensor - CO ₂ 5000ppm |