

# Frequently Asked Questions | FFAST FLEX™



## Table of Contents

1. General FAQs .....	2
-----------------------	---

## 1. General FAQs

### Q 1: What is the technical specification of FAAST FLEX?

A: The table below lists key technical specification of FAAST FLEX

#### General Specifications:

<b>Flow Sensor Number</b>	1 per channel		
<b>Level of Alarm</b>	Pre-Alarm & Alarm per channel		
<b>Area Coverage</b>	Single Chamber: 1,600m <sup>2</sup> (17,200 sq.ft) Dual Chamber: 2,000m <sup>2</sup> (21,527 sq.ft)		
<b>Pipe Network Layout</b>	<b>Single Pipe</b>	Linear pipe length:	1 x 105m (344 ft)
		Branch pipe length:	2 x 105m (344 ft)
	<b>Dual Pipe</b>		Linear pipe length:
		Branch pipe length:	4 x 105m (344 ft) 8 x 49m (161 ft)
<b>Sampling Holes</b>	<b>Single Chamber</b>	A, B, C: 5, 15, 32	
	<b>Dual Chamber</b>	A, B, C: 8, 28, 56	
<b>General Purpose Input (GPI)</b>	Reset, Disable, External Fault		
<b>Out-of-Box Configuration</b>	DIP Switches		
<b>Field Replaceable Components</b>	Sensing Module, Metal Filter, Front Cover, Aspirator, Internal Covers and Adaptor Set		
<b>Data Logging</b>	Device Info, Device Configuration, Device Status Logged Events and Data		
<b>Communication</b>	USB & Bluetooth		
<b>Warranty</b>	3 years		

#### Electrical Specifications:

<b>Detector Dynamic Sensitivity</b>	
<b>Supply Voltage</b>	24 V DC (18 - 30 V DC)
<b>Maximum Power Consumption</b>	Single Pipe: 400mA @24Vdc Dual Pipe: 450mA @24Vdc
<b>Relays</b>	3 per channel, Action, Alarm and Fault 2A @30V
<b>Detector Sensitivity Range</b>	0.05%obs/m to 6.56%obs/m (0.164%obs/ft – 21.5%obs/ft)

#### Environmental Specifications:

<b>Operating Conditions</b>	
<b>Operating Temperature</b>	-40 °C to 55 °C
<b>Sampled Air Temperature</b>	-40 °C to 55 °C
<b>Humidity</b>	10-93% RH
<b>Ingress Protection Rating</b>	IP40

For comprehensive specifications, please refer to the technical data sheets on the Xtralis website (Doc. no. 36502).

**Q 2: Does FAAST FLEX have filters? If so, how many and can they be cleaned?**

A: Each pipe inlet of the detector has 1 mesh type field replaceable filter. The FAAST FLEX filter mesh can be washed and cleaned.

**Q 3: Can FAAST FLEX be mounted without a mounting bracket?**

A: Yes, FAAST FLEX can be mounted directly on a surface via key holes on the back of the enclosure.

**Q 4: What are the different mounting options for FAAST FLEX?**

A: 2 mounting options (Upright & Inverted).

**Q 5: Would FAAST FLEX be able to give an indication if there is a blockage in a single hole on a pipe?**

A: Can detect 20% flow change in the pipe (ultrasonic flow sensing technology).

**Q 6: Is the FAAST FLEX Aspirator adjustable?**

A: Yes, to suit various environments.

**Q 7: What approvals does the FAAST FLEX have?**

A: VdS and EN 54-20. It is not UL certified.

**Q 8: Is the FAAST FLEX compatible with VESDA Pipe Clips?**

A: Yes, FAAST FLEX can work with the VESDA Pipe Clips.

**Q 9: Are there pipe packages available for FAAST FLEX?**

A: Yes, package options are available depending on the region and application.

**Q 10: I have an old ICAM IAS/ILS or FAAST LT unit on the wall; what do I need to do to replace it?**

A: The existing pipe network design shall be verified using pre-engineered network tables or PipeIQ with an appropriate FAAST FLEX model.

**Q 11: How are the optics protected in FAAST FLEX?**

A: Metallic mesh filters at the inlet and exhaust to protect detector optics and improve detector longevity.

**Q 12: What are the configuration modes of FAAST FLEX?**

A: Two configuration modes:

- Out-of-box with built in user-friendly DIP switch configuration for speedy commissioning
- Extended configuration via Bluetooth phone App for enhanced user experience.

**Q 13: What are the field replaceable components of FAAST FLEX?**

A:

- Sensing Module (FLX-SP-01)
- Metal Filter (FLX-SP-02)
- Aspirator (FLX-SP-04)

- Front Cover (FLX-SP-03-EN)
- Internal Covers (FLX-SP-05-EN)
- FAAST FLEX Adaptor Set (FLX-SP-06)

**Q 14: Is FAAST FLEX suitable for cold storage environments?**

A: Yes, FAAST FLEX is suitable for cold storage environments with -40 °C (-40°F) operating temperature. The detector has been tested and approved by VdS to operate at such low temperature inside freezer applications. For properly operated and maintained cold storage environments, the detector IP40 rating provides sufficient protection against ingress of crystallized water vapour.

**Q 15: How much does a FAAST FLEX detector cost?**

A: Please refer to your Regional Sales Director for pricing information.

**Q16: Does the two-pipe version have two aspirators or only one?**

A: One fan.

**Q 17: Is the branding Xtralis or System sensor?**

A: Xtralis.

**Q 18: Does two pipes mean two sectors or one sector?**

A: FAAST FLEX 2CH model has 2 sectors (i.e., 2 detection chambers).

**Q 19: Are Pre-engineered pipe tables and PipeIQ available for FAAST FLEX?**

A: Yes, PipeIQ will be available after the launch.

**Q 20: Which inline filter will be used with FAAST FLEX?**

A: The Xtralis in-line filter VSP-850 and System Sensor F-INF-25.

**Q 21: How can FAAST FLEX be integrated with 3rd parties?**

A: The first release supports relays only, whereas future releases will support Modbus interface, System Sensor & Notifier Advanced protocol, Clip for Chinese market and ESSER interfaces.

**Q 22: What are FAAST FLEX ordering codes?**

A: Refer to the Datasheet (Doc. No. 36502) for ordering codes.

**Q 23: What support material is available for FAAST FLEX?**

A:

Document Title	Document No.
FAAST FLEX TDS	36502
FAAST FLEX Product Brochure	36622
FAAST FLEX Product Guide	36639
FAAST FLEX Product Bulletin	36642
FAAST FLEX Engineering Specs	36885
FAAST FLEX Lift/Shaft Application Note	36745
FAAST FLEX Double Knock Application Note	36811
FAAST FLEX Refrigerated Design Guide	36701