

ASD Pipe VP-P-200 End of Life (EOL) Notice - EMEA

June 2026

Overview

As part of our ongoing portfolio management, we are discontinuing the VP-P-200 pipe in the EMEA region due to lower demand and consolidating into the VP-P-210 pipe, which provides equivalent performance. The VP-P-210 will remain available and can be ordered through our US distributors, ensuring continued support for our customers' needs.

Please note that VP-P-200 and VP-P-210 have the same performance specifications, as listed below:

Nominal Size	3/4" (20mm)
Average OD	1.050" (26.7mm)
Average ID	0.874" (22.5mm)
Pounds Per Foot	0.168

Operating Ratings:

Flammability Rating	V-O	UL 94 Flame Retardant
Limiting Oxygen Index	60	ASTM D2863
Flame Spread	0	ULC
Smoke Generation	0-25	ULC
Flame Travel	4	UL 1887
Optical Density	0.19 peak 0.03 Avg.	UL 1887
Heat of Combustion	7,700 BTU's/lb.	

Affected Products

The impacted product is shown in the table below:

Discontinued Products		Alternative Products	
SKU	Description	SKU	Description
VP-P-200	ASD PIPE 3/4", 10ft per pipe (20pcs)	VP-P-210	ASD PIPE 3/4", 15ft per pipe (14pcs)

Effective Date

The phase-out is **Effective Immediately**.

Contact

For any questions or concerns, please contact your Regional Sales Manager or Customer Service Representative.